

8. LED



Vapor Tight LED Low Bay

VLEDLB2-N

DIMENSIONS



Width: 14.61"



Width: 14.61" • 371mm Length: 51.91" • 1319mm Depth: 5.95" • 151mm

For critical applications, verify all dimensions with factory.



ORDERING

Standard with stainless steel latches. For pendant mounting. Stainless steel mounting brackets reduce installation time and eliminate the need for mounting holes in fixture body. Stainless steel V hooks simplify pendant mounting with chain or cable. For individual or continuous row with flexible conduit.

HOUSING

Heavy-duty unsaturated fiberglass reinforced polyester housing with poured in place gasketing. Flame class 5VA.

ELECTRICAL

<10% THD and include 5 year manufacturer's warranty. Operate on 120V-277V (UNV) unless specified otherwise.

SHIELDING

Glass clear diffuser is molded of UV stabilized impact resistant acrylic.

CERTIFICATION

All units bear UL label. Made in U.S.A. Suitable for damp location. ARRA and BAA compliant. IP67 Certified. National Sanitation Foundation (NSF) approved componenets. NEMA 4X rated. Factory hose-down tested at 1500 PSI, 1.4 gallons/minute @ 12-24". 5 YEAR LED WARRANTY.

<u>MODEL</u>	<u>LED CHANNELS</u>	<u>VOLTAGE</u>
VLEDLB2-N	135 Watts FLATBOARD ARRAY	UNV

LUMENS:
13467

OPTIONS:

- SSV – Stainless Steel V Hooks
- SSMB – Stainless Steel Mounting Brackets
- TP – Tamperproof Hardware
- HB6OY – 5' Cable Hanging Kit (other lengths available.)



JOB NAME:
FIXTURE TYPE:
MODEL NO: